Lake View Cemetery Foundation Installation and Repair Application

All footer installations, and footer repairs require this application to be completed. All installations and repairs must be inspected. Any repairs of tipped, and or cracked foundations require the existing foundation to be removed and a new foundation installed according to the specifications below. <u>No pour overs will be allowed.</u>

Monument Height	Depth in ground	Above Ground
12 inches or less	25 inches	5 inches
13 – 18 inches	31 inches	5 inches
19 - 36 inches	38 inches	5 inches
37 inches or higher	48 inches	5 inches

All Military monuments fall into the first category, 12 inches or less.

All Footers are to have two pieces of ½" re-rod placed horizontally ten inches from the top equally spaced front to back, and three inches from each end of the footer.

All footers will consist of 100 % concrete.

All footers are to be placed on the West twenty-four inches of the Lot/Plot. Each footer must be six inches longer, and six inches wider than the monuments length and width, and will project at least (5) five inches above the ground at the highest point. If there is a significant grade difference the most exposed side must be at least 36 inches in the ground.

The following information is required with needed signatures, and accepted by an official of Lake View Cemetery before any footers or repairs may be placed.

Monument Dealer & Phone Number _____

Purchaser Name & Phone Number _____

Lot Number and/or Lot Owner _____

Attach a sketch of the Lot with prior burials, and monuments noted. If unknown contact the Cemetery for assistance. (607-280-2099) (607-532-4902)

Attach a sketch of Monument(s) or attach a copy, including inscription on the monument, length, width, and height, also noting direction the monument will be read from.

Name & number of person responsible for repairing or installing the footer.

_____

Cemetery Official Signature, and Date accepted.

Application _____   _____

Footer _____   _____